


## Component size

Size unit: mm


Rectifier sandwich plate Z4S6-1XJ/...



- 1 2-way flow control valve
- 2 Rectifier sandwich plate
- 3 Name plate
- 4 O-ring 9.25x1.78( for oil port A、 B)

**Attention:**

The rectifier sandwich plate type Z4S6-1XJ/... can not be connected with the flow control valve 2FRM6A...-3XJ/... with external connection of the pressure compensator.



## Two Ways Flow Control Valve

Model: 2FRM...2XJ



- ◆ Size 10 to 16
- ◆ Maximum working pressure 315 bar
- ◆ Maximum working flow 160 L/ min

## Contents

Function description, sectional drawing	02
Models and specifications	03
Functional symbols	03
Technical parameters	04
Characteristic curve	05
Component size	06-07

## Features



- Optional pressure compensator stroke limiter
- Start-up jump reduction
- Lockable knob
- Flow control in both direction by means of rectifier sandwich plate

**Function description, sectional drawing**

2FRM model flow valve is two ways flow control valve which is composed of the pressure reducing valve and the throttle valve in series.

When the oil fluid flows into the valve, it is reduced pressure through the pressure reducing valve first and then throttled by the throttle valve. The flow of the flow valve is stable and unaffected by load changing because of the pressure compensation provided from the pressure reducing valve to the throttle valve. At the same time, the orifice is designed into thin blade shape to make little influence to the flow by temperature changing. When the flow valve and check valve is connected in parallel, the oil fluid can flow back in the opposite direction.

The rectifier sandwich plate Z4S is installed under the flow valve, it can stabilize the flow in both directions of the flow valve.



X-X section

- 1 Adjusting element
- 2 Throttle rod
- 3 Valve body
- 4 Orifice
- 5 Valve sleeve
- 6 Check valve
- 7 Reducing valve

03

**Models and specifications**

**Two ways flow control valve**

2FRM		-	2X	J			*
size 10	=10						
size 16	=16						
2X series, (20 to 29 series installation and connection size unchanged)		=2X					
Rekith		=J					
to 2L/min	=2L	flow range A → B					
to 5L/min	=5L						
to 10L/min	=10L						
size 10 to 16L/min	=16L						
to 35L/min	=35L						
to 50L/min	=50L						
to 40L/min	=40L						
to 60L/min	=60L						
size 16 to 80L/min	=80L						
linear to 100L/min	=100L						
to 125L/min	=125L						
to 160L/min	=160L						

more information in text

sealing material  
No code = NBR seals  
V= FKM seals  
(consult for other seals)

No code= pressure compensator, without stroke limiter  
B= pressure compensator, with stroke limiter

03

**Rectifier sandwich plate**



Z4S		-	1X	J		*
size 10	=10					
size 16	=16					
1X series (10 to 19 series installation and connection size unchanged)		=1X				
Rekith		=J				

more information in text

sealing material  
No code = NBR seals  
V= FKM seals  
(consult for other seals)

**Functional symbols**

①=Valve side ②=Subplate side



Technical parameters

Overview

Oil fluid	Mineral hydraulic oil or phosphate ester hydraulic oil
Oil temperature range °C	-30 to +80 (NBR seals) -20 to +80 (FKM seals)
Viscosity range mm <sup>2</sup> /s	10 to 800

Rectifier sandwich plate


Rated flow L/min	Size 10	Size 16
	50	160
Working pressure Mpa	to 31.5	
Weight kg	Size 10	Size 16
	3.2	9.3

Maximum flow L/min		Size 10				Size 16		
		10	16	25	50	60	100	160
Δ P with free return flow B → A q <sub>v</sub> -dependent		Size 10				Size 16		
		2.0	2.5	3.5	6.0	2.8	4.3	7.3
Flow control	Temperature stability -20~70 °C	±2% (Qmax)						
	Pressure stability (to ΔP=315) bar	±2% (Qmax)						
Working pressure at port A		bar to 315						
Minimum pressure drop		Size 10				Size 16		
		3...12				5...12		
Degree of contamination		μm 25 (Q<5L/min)				10 (Q<0.5L/min)		
Weight kg		Size 10				Size 16		
		5.6				11.3		


Characteristic curve

(Measured when using HLP 46,  $\vartheta_{\text{m}} = 40^\circ\text{C} \pm 5^\circ\text{C}$ )


Size 10




Size 10



Size 16




Size 16



Rectifier sandwich plate

Size 10

Flow from A → B (B → A)  
The pressure drop is same in both directions of flow



Size 16

